



NASA ExEP Resources Available for TDEM PIs

Nick Siegler Program Chief Technologist NASA Exoplanet Exploration Program (ExEP) Jet Propulsion Laboratory/California Institute of Technology

> Pre-Proposal TDEM-16 Briefing Telecon 01/26/17

> > CL#17-0324






- This presentation provides an overview of the ExEP resources located at JPL available to support a TDEM-16 proposal.
- The available resources, if appropriate for your needs, may help you more efficiently meet your milestone goals and reduce your proposal costs and schedule.

Unavailable Resources at JPL for TDEM-16

- HCIT-1 (dedicated to WFIRST)
- HCIT-2a (dedicated to the ExEP Decadal Survey Testbed)
- Starshade Lab facilities (deployable and optical shield testbeds, scatterometer)

Available Resources at JPL for TDEM-16

- HCIT-2b
- Vacuum Surface Gauge
- Microdevices Laboratory (MDL)







Available ExEP Resources at JPL for TDEM-16



High Contrast Imaging Testbeds (HCITs)


Exoplanet Exploration Program

Test Facility

- Two vacuum chambers with 1 mTorr capability
- Seismically isolated, temperature-stabilized ~ 10 mK at RT.
- Narrow or broad band coronagraph system demos
 - Achieved 3x10⁻¹⁰ contrast (narrowband)
- Fiber/Pinhole "Star" Illumination
 - -Monochromatic: 635, 785, 809, and 835 nm wavelengths
 - -2, 10, and 20% BW around 800 nm center
 - -Medium and high power super-continuum sources
- CCD camera (5e⁻), 13 μ m pixels
- Complete computer control with data acquisition and storage
- Coronagraph model validation & error budget sensitivities
- Remote access through FTP site



HCIT-1 Single-testbed capacity (5'x8')



HCIT-2 Two-testbed capacity (6'x10')

Availability for one testbed in HCIT-2 expected beginning of CY18




Wavefront Sensing & Control



Exoplanet Exploration Program

Nulling Algorithms

- Electric Field Conjugations (EFC) algorithms exist for single and dual DM control
- Demonstrated to < 10⁻⁹ contrast and 20% bandwidth
- Coupled to HCIT coronagraph models and DM calibration data for optimal efficiency



Best Results to Date

Band-Limited Coronagraph : 6 e-10, @ 3 λ/D with 10% BW 2 e-9, @ 3 λ/D with 20% BW

Shaped-Pupil Coronagraph: 1.2 e-9, @ 4 λ /D with 2% BW 2.4 e-9, @ 4 λ /D with 10% BW


PIAA Coronagraph: <1e-9, @ 2 λ /d with 0% BW

Vector Vortex Coronagraph: <1e-9, @ 3 λ /d with 0% BW

EFC Nulling and current performance

Deformable Mirrors

- Wavefront control and speckle nulling available with Xinetics PMN deformable mirrors.
 - Format sizes: 32x32mm, 48x48, and 64x64 mm with 1 mm pitch and 500 nm stroke size.
 - Continuous fuse silica facesheet polished to λ /100 rms
 - Two-DM configurations available



Xinetics DM

Availability expected beginning of CY18




Vacuum Surface Gauge




Exoplanet Exploration Program

Purpose: Accurate surface error measurement and deformable mirror calibration.

- Demonstrated optical surface measurement accuracy: ≤ 100 pm rms
- Customized Michelson interferometer set-up
 - Reference mirror w/ absolute position feedback
 - Frequency stabilized laser source
- Dedicated algorithms for wavefront extraction over > 10⁶ pixels



Vacuum Surface Gauge testbed



End-points of axes are [4.5,6.5] inches from table corners. Beam height = center of beamsplitter = 4.405 inches. Top of b.s. mount = 8.810. Lens cell dia = 3.480. Top of lens cell = 6.147 inches.

Surface Gauge optical layout



MicroDevices Laboratory (MDL)



Exoplanet Exploration Program




Figure 1. Microscope image (above) and AFM profile (below) of a micro dot patterned mask for JWST NIRCam coronagraph







Figure 2. Diffractive optical devices



Purpose: Precision sub-micron materials fabrication and characterization

Advanced fabrication and characterization techniques

- **Electron Beam Lithography**
- **Deep Reactive Ion Etching**
- ICP Cryo Etching of Black Silicon microstructures
- Scanning Electron Microscopy
- Precision Optical Microscopy
- Atomic Force Microscopy
- 2D and 3D profilometry

Light suppression mask fabrication processes developed for:

- Micro dot patterned mask for JWST (Fig 1)
- Diffractive optical structures for spectrometer gratings and other computer generated holograms (Fig 2)
- Shaped pupil masks with fine structures and slits for transmission geometry (Fig 3)
- Shaped Pupil masks with black silicon structures in reflective aluminum background (Fig 4)
- LOWFS masks (Fig 5) incorporating a black silicon region ٠ (Fig 6) as well as shaped aperture through a silicon wafer
- Achromatic focal plane masks with deep diffractive structures (Fig 7)
- PIAACMC mask (Fig 8)
- Hybrid Lyot mask for WFIRST(Fig 9)
- Starshade mask for Princeton testbed (Fig 10)






Figure 3. Transmissive slit Figure 4. Reflective and SP mask








Figure 5. LOWFS mask Figure 6. Black Si Microstructure




Figure 7 . Achromatic Focal Plane Masks (AFPM)






Figure 8 . PIAACMC mask Figure 9 . Hybrid Lyot mask







Gaining Access to the ExEP Resources at JPL





- Submit preliminary Statement of Work (SOW) for use of ExEP resources to Brendan Crill no later than <u>March 3, 2017.</u>
 - Follow SOW questionnaire on next page.
- Schedule telecon with Brendan Crill between <u>March 3 10, 2017</u> to discuss use of the resources of interest and to obtain costing guidelines.
- We will evaluate workforce, labor, and infrastructure access required across all received SOWs.
 - Assessment will be provided to Doug Hudgins for consideration in proposal review process.
- Brendan Crill will supply the proposal PI a Letter of Commitment for use of any ExEP resources.
 - PIs are to include both the SOW and the Letter of Commitment in their proposal.
 - HCIT will provide labor to set up testbeds; additional labor and procurements specific to your proposal must be costed within the proposal to support the work.





- **1.** Brief description of the proposed TDEM
- 2. What resources are requested?
- 3. Milestone (s) to be accomplished and performance goals
- 4. Brief description of how the work will be conducted
- 5. Period(s) and preferred dates, if any, over which the resource is requested, stating whether in vacuum or air for testbeds. Include any time required for preparatory work.
- 6. A list of the personnel, expertise, and level of effort (if any) who will assist in the use of the resource.
- 7. Any anticipated changes to the resource needed to accommodate your demonstrations.
- 8. List of items needed for all testbed modifications. Identify items you will be procuring within your proposal's budget and provide approximate cost of needed items.
 - a. Otherwise, state that no additional procurements will be necessary for the use of the infrastructure under consideration.
- 9. Provide any other relevant information or constraints.





For questions concerning use of ExEP technology resources or requests for more detail contact:

Dr. Brendan Crill Jet Propulsion Laboratory 4800 Oak Grove Drive Pasadena, CA 91109

Office: (818) 354-5416 Email: <u>bcrill@jpl.nasa.gov</u>

Copyright 2017 California Institute of Technology. Government sponsorship acknowledged.